


Franko 10W-100W

Franko 10W-100W




Gövde Body	Elektrostatik toz boyalı alüminyum enjeksiyon Electrostatic powder coated aluminium injection	Giriş Gerilimi Input Voltage (V)	220-240	Frekans Frequency (Hz)	50-60
LED	SMD	Renk sel ger. ind. Colour Ren. In. (CRI)	>80	IP Koruma IP Protection	IP65
Reflektör Diffuser	Simetrik, PMMA, UV dayanımlı, alüminyum Symmetric, PMMA, UV protection, aluminium	Güç Faktörü Power Fac. (cos φ)	> 0.90	RAL Kodu RAL Code	9005
Optik Kapak Diffuser	Temperli cam Tempered glass				
Sürücü Driver	Pelsan marka yüksek verimli Pelsan high efficiency driver				

Işık Şiddeti Dağılım Eğrisi Light Distribution Curve



180,0 — 0,0 100 W LED η:100,00%
270,0 — 90,0

Teknik Çizim Technical Drawing



Kullanım Alanları Fields of Application



Armatürlere ait büyüklükler Product Details

Ürün Kodu Code No	Güç Power (W)	Işık Akısı Luminous Flux (lm)	Renk Sıcaklığı Colour Tem. (K)	Etkinlik Faktörü Luminous Effic. (lm/W)	Boyutlar Dimensions (mm) a b c	Koli Adedi Pcs/Pack	Koli Hacmi Package Vol. (m ³)	Koli Ağırlığı Package Weight (kg)
5617 1031	10	700	6500	70	84x110x38	40	0,029	14
5617 1041	20	1540	6500	77	140x180x45	20	0,038	15
5617 1051	30	2310	6500	77	85x223x50	10	0,033	15
5617 1071	50	4350	4000-6500	87	230x285x65	6	0,0042	15
5617 1081	70	6090	4000-6500	87	288x335x78	4	0,0075	12
5617 1091	100	8800	4000-6500	88	288x335x86	4	0,0082	14