





Teknik Çizim

Technical Drawing



Bağlantı Şeması

Connection Scheme



Balastlar Ballasts

Floresan Balastlar

Fluorescent Ballasts

Özellikler

- Düşük watt kayıplı silisili sac ve otomatik paketleme sistemi sayesinde sessiz çalışma
- İletkenliği yüksek H sınıfı emaye kaplı bakır telleri ile uzun عمر ve düşük güç kaybı
- Yanmaz plastik aksam
- Üretim prosesi boyunca etkin kalite kontrol denetimi yapılarak eksiksiz ve hatasız üretim
- Rutubetten, UV ışınlarından, tozdan etkilenmeyen izolasyon verniğiyle korozya karşı koruma
- Yüksek frekans yayamasından dolayı elektromanyetik uyumluluk

Opsiyonlar

Farklı gerilim(220/230/240) ve frekanslarda(50/60Hz) üretim
15 / 20W balastlar için 110/120 V üretim

Specifications:

- Low watt-loss, quiet operation thanks to siliceous sheet and automatic packaging system
- Long-lifetime and low-loss with highly conductive H-class enamelled copper wires
- Non-flammable plastic components
- Effective quality control throughout the production process ensuring complete and fault-free production
- Protection against corrosion with moisture, ozone and dust proof insulating varnish
- Does not emit high frequency waves and thus problem-free in terms of electromagnetic compatibility and harmless to human and animal life

Options

- Production in different voltages (220/230/240) and frequencies (50/60Hz)
- 110/120 V production for 15/20W ballasts

Ürün Özellikleri Product Details

Ürün Kodu Code No	Tip Type	Güç Power (W)	Gerilim Voltage (V)	Akım Current (A)	Lamba Tipi Lamp Type	Kondansatör Capacitor (μ F±10 250 V)	Güç Faktörü Power Factor	Boyutlar Dimensions (mm) a b c d	Ağırlık Weight (kg)	Hacim Volume (m ³)	Koli Adedi Pcs/Pack
5911 3581	B1	40	230	0.430	TL-D	4.5	0.46	155x42x32,5x145	30.3	0.007562	36
	B1			0.430	TL	4.5	0.46				
	B1			0.430	TL-E	4.5	0.46				
	B1			0.430	PL-L	4.5	0.46				
5911 3641	B2	15 W	230	0.330	TL-D 15	0.45	0.33	110x42x32.5x101	20.4	0.005605	36
5911 3651	B2	20 W	230	0.370	TL-D 18	4.5	0.33	110x42x32.5x101	20.1	0.005605	36
	B2			0.370	TL-20	4.5	0.33				
	B2			0.370	PL-L 18	4.5	0.33				
	B2			0.370	TL-E 22	4.5	0.33				
5911 3671	B2	32	230	0.420	TL-E	5	0.41	110x42x32,5x101	20.4	0.005605	36
5911 3681	B2	40	230	0.430	TL-D	5	0.48	110x42x32,5x101	20.4	0.005605	36
	B2			0.430	TL	4.5	0.48				
	B2			0.430	TL-E	4.5	0.48				
	B2			0.430	PL-L	4.5	0.48				
5911 3691	B2	58	230	0.670	TL-D	7	0.46	155x42x32,5x145	21	0.00544	24
	B2	65	230	0.670	TL-D	7	0.51	155x42x32,5x145	21	0.00544	24
5911 3111	İnce	15	230	0.330	TL-D	4,5	0.33	160x29x26x150	20	0.004664	36
5911 3231	İnce	20	230	0.370	TL-D	4.5	0.33	160x29x26x150	20	0.004664	36
	İnce			0.370	TL	4.5	0.33				
	İnce			0.370	PL-L	4.5	0.33				
	İnce			0.370	TL-E	4.5	0.33				
5911 3251	İnce	32	230	0.425	TL-E	4.5	0.41	160x29x26x150	20	0.004664	36
5911 3241	İnce	40	230	0.430	TL-D	4.5	0.48	160x29x26x150	20	0.004664	36
	İnce			0.430	TL	4.5	0.48				
	İnce			0.430	TL-E	4.5	0.48				
	İnce			0.430	PL-L	4.5	0.48				